



CERTIFICATE NUMBER	22-2313858-PDA
EFFECTIVE DATE	07-Dec-2022
EXPIRY DATE	06-Dec-2027
ABS TECHNICAL OFFICE	London Engineering Department

CERTIFICATE OF Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

ROCKWOOL INTERNATIONAL A/S

located at

HOVEDGADEN 584, , DK-2640 HEDEHUSENE, Denmark

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product: Fire Retarding Deck
Model: Steel Deck H-60
Endorsements:
Tier: 3 - Type Approved, unit certification not required

This Product Design Assessment (PDA) Certificate remains valid until 06/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau Of Shipping

Karthik Subramanian,Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010)

ROCKWOOL INTERNATIONAL A/S

HOVEDGADEN 584

DK-2640 HEDEHUSENE

Denmark

Telephone: +31 475 353915

Fax:

Email: math.mourmans@rockwool.com

Web: www.rockwool-rti.com

Tier: 3 - Type Approved, unit certification not required

Product: Fire Retarding Deck

Model: Steel Deck H-60

Endorsements:

Intended Service:

Fire Retarding Decks

Description:

H 60 Steel Decks is insulated with two layers of mineral wool panel's i.e. Rockwool SeaRox SL 660 (exposed surface) 50 mm thick each and having density of 150 kg/m³, fitted on the deck plating and below the stiffeners. The mineral wool panels are secured to the deck plate and to the stiffeners by means of steel pins and washers welded with pitch ranging from 100 up to 400 mm.

Rating:

H-60

Service Restriction:

1. Unit Certification is not required for this product.
2. Continuous compliance with the statutory requirements requires maintenance of the Full Type Approval. The scope of Type Approval is to comply with MSC.1/Cir. 1221 dated 1 December 2006.

Comments:

1. The Manufacturer has provided a declaration about the control of, or lack of Asbestos in this product.
2. Unless specifically directed by the Administration, this approval is not to be construed as a substitute of a flag Administration's approval for the purpose of SOLAS (2020 Consolidated Edition) as amended.
3. In those instances where flag administration may have their own specific requirements, flag Administration's approval may be required
4. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.

Notes/Drawing/Documentation:

Tested by RINA Test report No N.2008 CS 016071/1 Dated 9 March 2009

Terms of Validity:

This Product Design Assessment (PDA) Certificate remains valid until 06/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

ABS Rules for Condition of Classification 2022: 1-1-4/7.7, 1-1-A3 & A4;

ABS Rules for Condition of Classification -Offshore Units and Structures 2022: 1-1-4/9.7, 1-1-A2 & 1-1-A3

ROCKWOOL INTERNATIONAL A/S

HOVEDGADEN 584

DK-2640 HEDEHUSENE

Denmark

Telephone: +31 475 353915

Fax:

Email: math.mourmans@rockwool.com

Web: www.rockwool-rti.com

Tier: 3 - Type Approved, unit certification not required

National:

NA

International:

IMO FTP Code Resolution A.754(18) (adopted on 4 Nov 1993), with the adoption of hydrocarbon fire curve
Revalidated in accordance with section 5.2 of IMO Resolution MSC.307(88) (adopted on 3 December 2010) - 2010
FTP Code

Government:

NA

EUMED:

NA

OTHERS:

NA



CERTIFICATE NUMBER	22-2313858-PDA-DUP
EFFECTIVE DATE	07-Dec-2022
EXPIRY DATE	06-Dec-2027
ABS TECHNICAL OFFICE	London Engineering Department

CERTIFICATE OF Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

ROXUL ROCKWOOL INSULATION INDIA PVT. LTD.

located at

**PLOT Z/4 DAHEJ SEZ, , DAHEJ, DISTRICT BHARUCH, GUJARAT,
India, 392130**

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product: Fire Retarding Deck
Model: Steel Deck H-60
Endorsements:
Tier: 3 - Type Approved, unit certification not required

This Product Design Assessment (PDA) Certificate remains valid until 06/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau Of Shipping

Karthik Subramanian,Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010)

ROXUL ROCKWOOL INSULATION INDIA PVT. LTD.

PLOT Z/4 DAHEJ SEZ

DAHEJ, DISTRICT BHARUCH GUJARAT

India 392130

Telephone: +91 610835284

Fax:

Email: lukas.Vonsik@rockwool.com

Web: www.rockwool-searox.com

Tier: 3 - Type Approved, unit certification not required

Product: Fire Retarding Deck

Model: Steel Deck H-60

Endorsements:

Intended Service:

Fire Retarding Decks

Description:

H 60 Steel Decks is insulated with two layers of mineral wool panel's i.e. Rockwool SeaRox SL 660 (exposed surface) 50 mm thick each and having density of 150 kg/m³, fitted on the deck plating and below the stiffeners. The mineral wool panels are secured to the deck plate and to the stiffeners by means of steel pins and washers welded with pitch ranging from 100 up to 400 mm.

Rating:

H-60

Service Restriction:

1. Unit Certification is not required for this product.
2. Continuous compliance with the statutory requirements requires maintenance of the Full Type Approval. The scope of Type Approval is to comply with MSC.1/Cir. 1221 dated 1 December 2006.

Comments:

1. The Manufacturer has provided a declaration about the control of, or lack of Asbestos in this product.
2. Unless specifically directed by the Administration, this approval is not to be construed as a substitute of a flag Administration's approval for the purpose of SOLAS (2020 Consolidated Edition) as amended.
3. In those instances where flag administration may have their own specific requirements, flag Administration's approval may be required
4. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.

Notes/Drawing/Documentation:

Tested by RINA Test report No N.2008 CS 016071/1 Dated 9 March 2009

Terms of Validity:

This Product Design Assessment (PDA) Certificate remains valid until 06/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

ABS Rules for Condition of Classification 2022: 1-1-4/7.7, 1-1-A3 & A4;

ABS Rules for Condition of Classification -Offshore Units and Structures 2022: 1-1-4/9.7, 1-1-A2 & 1-1-A3

ROXUL ROCKWOOL INSULATION INDIA PVT. LTD.

PLOT Z/4 DAHEJ SEZ

DAHEJ, DISTRICT BHARUCH GUJARAT

India 392130

Telephone: +91 610835284

Fax:

Email: lukas.Vonsik@rockwool.com

Web: www.rockwool-searox.com

Tier: 3 - Type Approved, unit certification not required

National:

NA

International:

IMO FTP Code Resolution A.754(18) (adopted on 4 Nov 1993), with the adoption of hydrocarbon fire curve
Revalidated in accordance with section 5.2 of IMO Resolution MSC.307(88) (adopted on 3 December 2010) - 2010
FTP Code

Government:

NA

EUMED:

NA

OTHERS:

NA